

# U10

# Light Commercial & Residential Gas Meter



## PRODUCT INFORMATION

The U10 is a light commercial & residential gas meter from EDMI's Gas Series. The U10 is rated to 10.0 m³/hr of gas @ 125 Pascal loss across the meter with a high level of accuracy due to its large cyclic capacity, radial valve covers and a magnetic drive which all combine to give superior accuracy retention and stability throughout the life of the meter.



# **KEY FEATURES**









# U10 Gas Series

# Light Commercial & Residential Gas Meter



# **SPECIFICATIONS**

#### **COMPLIANCE**

- AS 4647
- EN 1359

#### **CAPACITY**

- Gas: 10.0m3/hr (SG 0.64) @ 125 Pa Loss
- Air: 8.0m³/hr @ 125 Pa Loss

#### **ACCURACY**

- $< \pm 1.0\% 1.2 \text{m}^3/\text{hr}$  to  $8.0 \text{m}^3/\text{hr}$
- < ± 3.0% @ Qmin

#### **REPEATABILITY**

• < 0.2% Typical

#### **PRESSURE RATING**

• 25kPa (50kPa Option Available)

#### **CYCLIC CAPACITY**

• 2 Litre

#### **PROVEN RELIABILITY**


- Low Oscillation and Pressure Loss Characteristic Minimises Wear
- Large Diaphragm Area Provides Increased Driving Force
- Robust Materials Resistant to Environmental Effects
- Magnetic Index Drive Superior Leak Tightness


### TAMPER RESISTANT

- Security Seal on Body & Index
- Tamper-proof Magnetic Index Drive

#### **ENVIRONMENTAL**

- Temperature Range: -10°C to +65°C
- Relative Humidity: Up to 95%
- Corrosion Resistant (AS 2331, 1000hr Salt Spray)
- UV Resistant (AS 4647, EN 1359)
- Ingress Protection: IP55





#### **OUTPUT**


- Mechanical Metric Index XXXXX.XXX m3
- Pulse-ready Magnetic Output: 1Pulse = 10L
- Tamper-proof Reed Switch Reading Head Optional


#### **PHYSICAL DIMENSIONS**

- Connections: 1', 11tpi Thread to BS746 with 6' Centres
- Size: 234mm (W) x 252mm (H) x 205mm (D)
- Weight: Approx. 3.5kg

#### **MATERIALS**

- Body: DA401 Diecast with Polyester Powder Coat
- Element: Tern-coated Pressed Steel Body
- Bearings: Moulded Acetal
- Diaphragm: Rubber Moulded with Polyester Reinforcement
- · Valves & Grids: Phenolic
- Index Cover: UV Stabilised Polycarbonate
- Gears & Pinions: UV Stabilised Acetal
- Seals: Nitrile
- Links & Arms: Plated Steel







## **EDMI Limited**

47 Yishun Industrial Park A, Singapore 768724
Tel: +65 6756 2938 | Fax: +65 6756 0125
sgmarketing@edmi-meters.com
sgtechsupport@edmi-meters.com

## **EDMI Gas Pty Ltd**

7 Fowler Road, Dandenong, Victoria, Australia 3175 Tel: +613 9794 6000 | Fax: +613 9706 0055 gassales@edmi.com.au